### **FOSS**

## BacSomatic™

### Integrated bacteria and somatic cell count







BacSomatic<sup>™</sup> provides rapid hygiene testing of milk. BacSomatic is the first-ever integrated bacteria and somatic cell tester and offers full automation for minimal reagent handling and consistent test results.

#### Integrated bacteria and somatic cell tester

Automatic and fast alternative to manual assay, providing instant, simultaneous results for individual bacteria and somatic cell count within 9.5 minutes and 1.5 minutes for somatic cell count alone.

#### More accurate than alternative methods

A fully automated procedure avoids the risk of human error and inconsistency, while ready-to-use reagents in an enclosed bag system, ensure the exact same dosage for every measurement. A sensor in the reagent bag indicates the number of available tests remaining. The unique reagent concept includes control samples for quality assurance and GLP. Online remote monitoring ensures consistent performance and high uptime.

#### Simple and flexible to use

Built on a long heritage of FOSS analytical technology and backed by global FOSS support, BacSomatic combines robust performance with a modern interface. Very easy-to-use with intuitive touch-screen operation for smarter money-saving decisions on how to use milk.

#### Sample types

Raw cow's milk, buffalo milk and goat milk

#### **Parameters**

Individual Bacteria Count (IBC) Somatic Cell Count (SCC)

#### **Technology**

Flow cytometry technology, counting individual bacteria cells and somatic cells.

The IBC results can be converted to CFU results. BacSomatic software includes an easy and rapid tool to develop a robust conversion table between IBC and CFU.

#### **Approvals**

EURL/Microval FDA/NCIMS In compliance with ISO/IDF standards

# Specifications

Feature	Specification		
Analysis time	9.5 minutes for IBC, 1.5 minutes for SCC		
Analysis capacity	SCC and IBC: 15 samples/hour IBC only: 15 samples/hour SCC only: 40 samples/hour		
Sample intake	IBC & SCC: 7.2 ml IBC: 6.4 ml SCC: 2.5 ml		
Sample temperature	2 - 42 °C (35.6-107.6 °F) (preserved) 2 - 4 degrees °C (non preserved)		
Sample quality	Raw milk of normal composition and good quality. Unpreserved or preserved with azidiol		
Carry-over effect	<1% relative, usually <0.5% (uncompensated) IBC and SCC		
Working factor	IBC: 100 and SCC: 100		
Measuring range	IBC: 5,000-20 mill. IBC/ml (approx. 1,500 to 10 mill CFU/ml) SCC: 0-10 mill. cells/ml		
Performance range	IBC: 10,000 - 10 mill. IBC/ml SCC: 100,000 - 1.5 mill. cells/ml		
Accuracy	IBC: Typical Sy,x $<$ 0.25 log units from SPC (standard plate count) SCC: $<$ 10% relative mean difference form Direct Microscopic SCC		
Reference or anchor method	Standard Plate Count (SPC) EN-ISO 4833-1:2013		
Dimensions (w x h x d)	400 x 400 x 400 mm		
Weight	25 kg		
Space requirements (w x d)	Approx. 600 x 630 mm		
Power supply	110 - 240 V AC, 50/60 Hz		
Power consumption	max 190 VA		
Water supply for preparation	Purified water ( $<5~\mu\text{S/cm}^3$ ) The instrument does not require a direct connection to water tap but for chemical preparations ultra pure de-mineralized water must be available		
Waste	Max 1 I		
Ambient temperature	Ambient temperature 5 - 35 °C (41 - 95 °F)		
Relative humidity	<93% RH		
Instrument management			
Networking software	FossManager™		

Repeatability			
Range (IBC/µI)	S <sub>r</sub> (log-units)	Typical S <sub>r</sub> (log units)	
10 - 50	0.07	0.06	
51 - 200	0.05	0.04	
>200	0.04	0.02	
Entire range	0.05		
Reproducibility (between instruments)			
Range (IBC/µI)	S <sub>R</sub> (log-units)	Typical S <sub>R</sub> (log units)	
10 - 50	0.11	0.08	
51 - 200	0.07	0.06	
>200	0.06	0.04	

Repeatability			
Range (SCC/µl)	CV, %		
100 - 299	6		
300 - 499	4		
>500	3		
Reproducibility			
Range (SCC/µl)	S <sub>R</sub> , %		
100 - 299	7		
300 - 499	5		
>500	4		

FOSS

Tel.: +45 7010 3370

 $in fo @foss. dk \cdot www. foss analytics. com\\$ 

GB, August 2021