

Transport Systems

B Medical Systems | MT Range

Transport Systems for the safe transport of temperature-sensitive products
> according to ADR | RID | IMDG | ICAO-TI | IATA-DGR









SAVING LIVES
THROUGH RELIABLE
AND INNOVATIVE
TECHNOLOGY

Blood Management Solutions



Transport Systems

B Medical Systems | MT Range

6 models • Volume 2.2 > 90 L • According to ADR | RID | IMDG | ICAO-TI | IATA-DGR

In conformity with national and international guidelines offering reliability, efficiency and safety at an optimal price.



Designed for intensive use

- The special transport boxes, made from rotationally moulded polyethylene (a literally indestructible synthetic), feature an extraordinarily sturdy casing that is almost impervious to external forces, e.g. caused by bumps and falls, whose sturdiness has been proven in drop tests
- The corrosion free material offers easier and safer handling and is light weight. All transport systems can easily and thoroughly be cleaned and disinfected with conventional disinfectants. There are no inaccessible corners or areas inside the transport systems
- The clasps can be sealed or equipped with locks and are therefore protected against unauthorised access during transport



O Highest insulation value





• Due to the outer casing's self-insulation against the environment, the B Medical Systems transport systems maintain a stable temperature even at higher ambient temperatures

Transport Systems for the safe transport of temperature-sensitive products. The model range MT consists of five passive transport systems and one active transport box, working with a compressor. B Medical Systems transport systems are ideal for intensive use with many transport applications, even under difficult climatic conditions. MT models conform with the European agreement on the international transport of hazardous goods by Road (ADR), by Rail (RID), by sea (IMDG) and with the International agreement for air transport (ICAO-TI / IATA-DGR).

For all passive transport boxes eutectic cooling systems are available as an option (-32°C, +4°C, +22°C and +37°C).











AVAILABLE SOPS:

- Process description and standards operating procedures for the transport of blood preparations using the transport systems mentioned above
- Conditioning of cooling elements
- Visual inspection
- Technical inspection
- Charging with cooling elements

Externally validated ambient temperature ranges: +10°C and +32°C (over 24 hours)

As minimum or maximum limits, these temperature ranges cover more than 90% of the transport scenarios imaginable. The lower limits of the typical number of blood bags for the respective container sizes were chosen as charges. These low charge levels are more unstable and the resulting test readings are significantly more telling with respect to critical temperature ranges. With increasing charges, the preparation's temperatures in the secondary (inner) container become increasingly stable.

External validation of "Maximum Cold Life" for the ambient temperature ranges of +32°C and +43°C

These ambient temperature ranges were chosen according to the validation parameters set by the WHO. As maximum limits including a safety margin, these temperature ranges cover all imaginable transport scenarios. Because it is the objective of the validation to determine the maximum operating time, so the upper limits of the typical number of blood bags for the respective container sizes were chosen as charges. With decreasing charges, the reliable operating time slowly decreases.



DECLARATION OF CONFORMITY (IN ACCORDANCE WITH ADR / RID / IMDG / ICAO-TI / IATA-DGR)

- European agreement concerning the international carriage of dangerous goods by road (ADR) and by railway (RID), directive 2008/68/EC
- European agreement concerning the international carriage of dangerous goods by sea transport (IMDG), directive 2002/84/EC
- International agreement for air transport (ICAO-TI / IATA-DGR)

MT 2, 4 & 12 may contain goods of packing groups I, II and III. MT 8 & 25 may contain goods of packing groups II and III.

Basis:

MT 2: Certificate N° 150151
 MT 4: Certificate N° 150153
 MT 8: Certificate N° 150152
 MT 12: Certificate N° 150154
 MT 25: Certificate N° 150155

Test reports of the accredited test laboratory IBE-BVI, Belgium.



Technical DataGeneral features













MT 2	MT 4	MT 8	MT 12	MT 25	MT 100
		D			A .: (C

Cooling systen	n			Passive			Active (Compressor
Gross volume (I)		2.2	8	20	24	44	90
Storage capac	city (bags)	1 (450ml) 2 (270ml)	4 (450ml) 6 (270ml)	8 (450ml) 14 (270ml)	15 (450ml) 25 (270ml)	25 (450ml) 40 (270ml)	48 (450ml)
Cald Life	at +32°C	up to 22 h	up to 46 h	up to 57 h	up to 96.14 h	up to 109 h	-
Cold Life	at +43°C	up to 17 h	up to 32.5 h	up to 16.39 h	up to 56.5 h	up to 74 h	-
Dimensions	External	210 x 250 x 150	299 x 362 x 283	437 x 588 x 288	499 x 550 x 475	499 x 710 x 550	1000 x 520 x 800
H x W x D (mm)	Inner	130 x 190 x 90	186 x 260 x 156	245 x 460 x 180	270 x 340 x 260	264 x 496 x 334	450 x 306 x 545
	Interior container	125 x 180 x 40	135 x 245 x 90	167 x 345 x 132	192 x 310 x 237	192 x 390 x 237	-
Net weight - e	empty (kg)	1.2	3.1	6.8	11.7	15.9	44
Gross weight - fully stocked (kg)		2.1	7.3	16.4	23.3	38.9	66
Insulation thic	kness (polyurethane)	30 mm	23-27 mm	50-60 mm	90-105 mm	90-105 mm	50 mm
Material	Outer / Interior	Polyethylene					
	Interior container	Polystyrene			Stainless steel		-

Operating temperature		+4°C or +22°C		
Application I	range (ambient temperature)	-2°C to +43°C		
Voltago	AC (mains)	100 V to 240 V (50/60Hz)		
Voltage	DC (battery)	12 V and 24 V		
Power		100 W		
Average run at +4°C interior t		28% at +25°C 60% at +43°C		
EMC directiv	re	2014 / 30 / EU		
Low voltage	directive	2014 / 35 / EU		











EquipmentStandard & optional

		MT 2	MT 4	MT 8	MT 12	MT 25	MT 100
Cooling	at 0.3 L	● 2 ○ 40	3 040	-	-	-	-
element	at 0.6 L	-	●2 ○24	●4 ○24	● 14 ○ 24	● 24 ○ 24	-
nterior	Polystyrene	1	1	1 (with lid)	-	-	-
ontainer	Stainless steel	-	-	-	1 (with lid)	1 (with lid)	4 (baskets)
ecuring plastic	r frame	-	-	-	-	• 1	-
Carrying strap ((adjustable)	1	1	1	-	-	-
Document compartment	Front	-	2	-	-	-	-
	Back	-	1	-	-	-	-
Eutectic cooling tests available upor		0	\circ	\circ	\circ	0	-
Temperature D ogTag / Testo	ata Logger	0	0	0	0	0	\circ





•
•
•
•
•
•
•

For long-term, temperature controlled transport

B Medical Systems | Eutectic Cooling System

B Medical Systems Eutectic Cooling

Elements are heat accumulation elements, containing a so-called phase change material (PCM). The PCM stores latent heat at the required temperature at phase change (liquid / solid). The stored product will therefore remain at a near constant temperature for a specific period of time, without requiring active temperature control. The Eutectic Cooling Elements must be charged for the specified temperature prior to each use, and are available in 2 sizes: 0.3 L & 0.6 L.

THE PHASE CHANGE
MATERIAL (PCM)
ALLOWS FOR SAFE
TRANSPORT DURING ALL
SEASONS. FROM WINTER
TO SUMMER, THE
PCM HAVE THE SAME
"MELTING POINT".

Tested according to specifications of the European Commission/ "Guide to the preparation, use and quality assurance of blood components"

The above picture shows the MT 4 with eutectic cooling elements and aluminium frame as an example. The elements are available separately as an option.

It's also possible to order our passive models as ready-equipped eutectic versions. Please contact us for details.



Eutectic Cooling Elements			PCM -32	PCM +4	PCM +22	PCM +37
Colour			Orange	Blue	Green	Yellow
Nominal			-32°C	+4°C	+22°C	+37°C
Application			< -30°C	+2°C > +8°C	+15°C > +25°C	>+35°C
Preconditionin	g temperature /	time	-40°C / > 24h	+4°C/>24h	+22°C / > 24h	+37°C / > 24h
			Plasma	RBC	Unscreened blood	Whole blood
Cold life of B Me with Eutectic Cod	dical Systems Tran oling System	sport Boxes	• • •	• • •	• • •	• • •
MT 4 - ET	Number of charged units		2	8	10	10
fully equipped with Eutectic	Ambient temperature	-10°C	> 24h	11 h 18	2 h 33	2 h 08
Cooling System 4 x 0.3 L		+22°C	12 h 33	18 h 36	-	15 h 02
and 1 x 0.6 L		+43°C	5 h 30	7 h 33	4 h 09	0 h 46
	Number of charged units		6	8	2	20
MT 8 - ET fully equipped	Ambient temperature	-10°C	> 24h	21 h 45	2 h 05	5 h 43
with Eutectic Cooling System		+22°C	> 24h	> 24h	-	> 24h
12 x 0.6 L		+43°C	> 24h	13 h 34	5 h 03	5 h 58
	Number of charged units		10	14	-	-
MT 12 - ET fully equipped	Ambient temperature	-10°C	> 24h	> 24h	-	-
with Eutectic Cooling System 14 x 0.6 L		+22°C	> 24h	> 24h	-	-
		+43°C	> 24h	> 24h	-	-
MT 25 - ET fully equipped with Eutectic Cooling System 18 x 0.6 L	Number of charged units		27	40	30	-
	Ambient temperature	-10°C	> 24h	> 24h	7 h 42	-
		+22°C	> 24h	> 24h	-	-
	temperature	+43°C	> 24h	> 24h	14 h 03	-

For perfect temperature control

B Medical Systems | Temperature Data Logger





Testo 174 T | 1-channel mini temperature data logger

- Incl. wall bracket, battery (2 x CR 2032 lithium) and calibration protocol
- High data integrity, even with empty battery
- Large data memory
- Watertight in accordance with IP65
- Temperature range -30°C to +70°C
- Starter set including logger, interface and software also available



Testo 176 T2 | 2-channel temperature data logger

- With connections for highly accurate external sensor (PT100) incl. wall holder, lock, battery and calibration protocol
- Large memory for 2 million measurement values
- large, easily legible display up to 8 years battery life
- Standard battery (AA) replaceable by user
- SD card slot
- Temperature range -50°C to +400°C

LogTag[®]



LogTag TRED30-16R | Temperature data logger

- For continious, tamper-proof temperature recording
- New, easy to read LCD display with 30 days summary
- Interchangeable external probe with high quality gold plated connector and built-in audible alarm
- Temperature range -40°C to +99°C (measurement range from an external probe)
- Standard battery (3V CR2032) replaceable by user



LogTag TRID30-7R | Temperature data logger

- For continious, tamper-proof temperature recording
- With 30 days statistic display
- Temperature range -30°C to +60°C

LogTag TRID30-7FW | Temperature data logger

 Vaccine Refrigerator Temperature Recorder with 30 day summary display compliant to WHO PQS specification E006/TR06.3





LogTag USB interface cradle

• For reading out the data recordings via PC

LogTag Remote probe

• 1.5 m cable, 140 mm tipped sensor







State-of-the-art technology for the exacting needs of the medical world

Reliable and innovative solutions for safe vaccination around the world







After Sales support and service

We strive to provide you with the highest standards of service; not only through our selected distributors and partners for all your maintenance and service but also our second line trouble shooting and after sales service. This Factory based group of engineers is there to help our partners and yourself to get the best solution for your cold storage needs.

Safe global blood management: from collection to transfusion, transportation, processing and storage

Our Global Expertise



SAVING LIVES THROUGH RELIABLE AND INNOVATIVE TECHNOLOGY

B Medical Systems (formerly Dometic Medical Systems) has more than 35 years' experience in the medical refrigeration sector.

The company, formerly known as Electrolux Medical Systems, was founded in 1979 when the World Health Organization approached Electrolux in Vianden, Luxembourg, to create a solution for the safe storage and transport of vaccines around the world. In 2001, Electrolux Medical Systems became part of the Dometic Group, and was renamed Dometic Medical Systems. Having established a legitimate reputation in the medical equipment industry, the company has also become a global leader in vaccine cold chain.

B Medical Systems S.à r.l.

17, op der Hei L - 9809 Hosingen, Luxembourg

Tel.: (+352) 92 07 31-1 Fax: (+352) 92 07 31-300 info@bmedicalsystems.com



Luxembourg, in the heart of Europe



www.bmedicalsystems.com

Ed 02/2018