Fossomatic™ 7

Somatic cell counting for raw milk testing



The Fossomatic[™] 7 provides accurate somatic cell counting (SCC) capability, handling up to 600 samples per hour. Results are delivered simultaneously in six seconds while unique hardware and software features boost proficiency in the laboratory.

Innovative 7th generation technology

Fossomatic 7 is a flexible solution allowing you to choose between manual or automatic reagent mixing. Rinse liquid refill without instrument stop allows you to keep operations running at all times. A modular design makes Fossomatic easy to clean and maintain and includes a sample conveyor without need for compressed air.

Higher performance and flexible solution

With a low working factor of 100, you can rely on the repeatability of results over time, whether running at 100 or 600 samples per hour.

Optimise instrument management with FOSS digital services

Ensure consistent performance of all instruments in your network and avoid downtime by making upgrades and adjustments while instruments continue to run. Protect your database and settings with automatic back up of data.



FOSS



Sample type

Raw milk from cows, goat, sheep and buffalo

Parameters

Total somatic cell count (SCC)

Technology

Flow cytometry technology that counts somatic cells. Can be integrated with the Milko-Scan™ 7 RM to form a CombiFoss™ 7.

Approvals

SCC in compliance with ISO/IDF standards. FDA/NCIMS and MicroVal (EURL) approved

Specifications

| Performance | |
|-----------------------------|---------------------------------------------------------------------------------|
| Measuring range | 0 – 10 mill cells/ml |
| Performance range | 0.1 – 1.5 mill |
| Repeatability | CV < 6% 100-299k SCC/ml CV < 4% 300-499k SCC/ml CV < 3% 500-1500k SCC/ml |
| Accuracy | < 10% relative mean diff. from DMSCC (Direct Microscopic Somatic Cell Count) |
| Carry-over | < 1% relative |
| Sample types | Fossomatic [™] 7: Cow, goat, sheep and buffalo milk |
| Application data | |
| Analysis capacity | 100, 200, 300, 400, 500 or 600 samples per hour |
| Sample intake | 2.5 ml (programmable 2.0 – 5.0 ml) |
| Required sample temperature | 30 - 42 °C (86-107.6 F) |
| Working factor | 100 |
| Instrument management | |
| Networking software | FossManager™ |

Standards and approvals

- Fossomatic[™] 7 is CE-labelled and complies with the following directives and regulations:
- EMC (ElectroMagnetic Compatibility) Directive 2014/30/EU
- LVD (Low Voltage) Directive 2014/35/EU
- Machinery Safety Directive 2006/42/EC
- Regulation (EC) 1272/2008 on classification, labelling and packaging of substances and mixture, CLP (EC)
- WEEE Directive 2012/19/EU
- Packaging and packaging waste Directive 94/62/EC
- REACH 1907/2006/EC

Fossomatic technology complies with:

- AOAC
- ISO 13366-2 / IDF 148-2:2006
- Laser approval (FDA), IEC 60825-1
- FDA/NCIMS and MicroVal (EURL) approved